

## Datasheet 4025001

### Aufbauleuchte Circel 600mm weiß Dim

Our 38/55 W Circel has been designed in a timeless design in a round shape. It has a glare-free illumination without any shadowing. Even the side covers radiate with. Our ceiling lamp finds its field of application in the most diverse places. However, it is mainly used in staircases due to its high switching resistance. Due to its quick mounting set, the mounting requires only a small amount of time, so our Circel is also very well suited as a project light. Especially important in the object: we offer 5 years warranty on the function and vouch for the high quality workmanship and durability of this lamp.



Dimmable: yes

Recommended dimmer: [www.sigor.de/dimmerliste](http://www.sigor.de/dimmerliste)


6.600 lm luminous flux [lm]  
38,00 Watt rated power  
3000 K colour temperature  
Ra>80 colour rendering  
<5 sdcn colour consistency  
110° beam angle

weiss Colour housing  
IP20 type of protection  
-10° - 40°C temperature range in operation

0.95 power factor  
230 V AC voltage  
50/60 Hz operating frequency  
170 mA current  
55 kWh/1000h energy consumption  
<0.5 s warm-up time up to 60% of the full light output  
<0.5 s starting time

Ø 50.000 h nominal life time  
L80B10 rated life time L70/B50  
0.8 lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**ENERGY**

**SIGOR**  
4025001

A

B

C

D

**E**

F

G

**55**  
kWh/1000h

2019/2015



4025001

Aufbauleuchte Circel 600mm weiß Dim



**Manual:**

[https://shop.sigor.de/media/pdf/4025001\\_manual.pdf](https://shop.sigor.de/media/pdf/4025001_manual.pdf)

as of: 18.12.2023

Page: 2