

Datasheet 4025101

Aufbauleuchte Circel 600mm weiß Dim

Our 38/55 W Circel has been designed in a timeless design in a round shape. It has a glare-free illumination without any shadowing. Even the side covers radiate with. Our ceiling lamp finds its field of application in the most diverse places. However, it is mainly used in staircases due to its high switching resistance. Due to its quick mounting set, the mounting requires only a small amount of time, so our Circel is also very well suited as a project light. Especially important in the object: we offer 5 years warranty on the function and vouch for the high quality workmanship and durability of this lamp.



Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste


6.600 lm	luminous flux [lm]
38,00 Watt	rated power
4000 K	colour temperature
Ra>80	colour rendering
<5 sdcn	colour consistency
110°	beam angle

weiss	Colour housing
IP20	type of protection
-10° - 40°C	temperature range in operation

0.95	power factor
230 V AC	voltage
50/60 Hz	operating frequency
170 mA	current
55 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.5 s	starting time

Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0.8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



ENERGY

SIGOR
4025101

A
B
C
D
E
F
G

55
kWh/1000h

2019/2015

as of: 18.12.2023

Page: 1



4025101

Aufbauleuchte Circel 600mm weiß Dim



Manual:

https://shop.sigor.de/media/pdf/4025101_manual.pdf

as of: 18.12.2023

Page: 2