

**Datasheet**  
**4029101**

**Feuchtraumleuchte Tricolour 1200 3-CCT**

Our specialist lighting dealers are pleased to present our new 'Tricolour' luminaire. This innovative luminaire has a dip switch that allows you to choose between three light colors: 3,000 K, 4,000 K or 5,700 K. The through-wiring cable with 3 × 1 mm<sup>2</sup> is already pre-installed, making installation quick and easy. The robust polycarbonate housing is IP65 and IK08 certified and offers protection against dust and water. The luminaire is supplied with stainless steel brackets as well as screws and plugs, so you have everything you need for installation. The high luminous efficacy of up to 120 lm/W and the long service life of up to 50,000 hours (L80/B10) make this luminaire an economical choice. It is also flicker-free and has a beam angle of 120°, which ensures pleasant lighting.



Dimmable no

4.000 lm	luminous flux [lm]
33,00 Watt	rated power
3000-5700 K	colour temperature
Ra>80	colour rendering
sdcn	colour consistency
120°	beam angle
weiss	Colour housing
IP65	type of protection
-10° - 40°C	temperature range in operation
0,95	power factor
220-240 V AC	voltage
50/60 Hz	operating frequency
143 mA	current
33 kWh/1000h	energy consumption
0,2 s	warm-up time up to 60% of the full light output
0,2 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life



**ENERGY**

**Sigor**  
4029101

A  
B  
C  
D  
**E**  
F  
G

**33**  
kWh/1000h

2019/2015



4029101

Feuchtraumleuchte Tricolour 1200 3-CCT



as of: 22.04.2024

Page: 2

**Sigor Licht GmbH** • Eichenhofer Weg 81 • 42279 Wuppertal  
Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61  
info@sigor.de • www.sigor.de

Handelsregister HRB 19472  
USt-IdNr.: DE 814574569  
WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer:  
Michael Perterer  
Robin Scheffel

