

Datasheet
4033701

Aufbauleuchte Square 260mm silber Sensor




Our 18 W **Square** has been designed in a timeless square design. It has a glare-free illumination without the formation of shadows, even the side covers radiate with. Our ceiling lamp finds its field of application in the most diverse places. However, it is mainly used in staircases due to its high switching resistance. Due to its quick mounting set, the mounting requires only a small amount of time, so our Square is also very well suited as a project light. Especially important in the object: we offer 5 years warranty on the function and vouch for the high quality workmanship and durability of this lamp.



Dimmable no

2.100 lm	luminous flux [lm]
18,00 Watt	rated power
3000 K	colour temperature
Ra>80	colour rendering
<5 sdcms	colour consistency
110°	beam angle
silber	Colour housing
IP20	type of protection
-10° - 40°C	temperature range in operation
0.95	power factor
230 V AC	voltage
50/60 Hz	operating frequency
80 mA	current
18 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0.8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
4033701

A	
B	
C	
D	
E	← E
F	
G	


18
kWh/1000h

2019/2015



4033701

Aufbauleuchte Square 260mm silber Sensor



Manual:

https://shop.sigor.de/media/pdf/4033701_manual.pdf

as of: 18.12.2023

Page: 2

