

Datasheet 4035001

Aufbauleuchte Split 270mm silber



Dimmable no

Our 24/18 W **Split** has been designed in a timeless round design. It has a glare-free illumination, without any shadow formation, even the side covers radiate with. By means of DIP switches built into the housing, the two power levels can be changed from 2,000 lm to 2,500 lm. The same principle follows the change of light color from 3,000 K to 4,000 K. If you want to connect several Split with each other, the ceiling lights will help you with its integrated connector for through-wiring. The additional connection cables are led off laterally and or centrally. Our ceiling light finds its application in a variety of places. Mainly you will use but due to the IP54 at the house or under the roof, such as for example as a house entrance lighting. Through your quick mounting kit needs the attachment only a small amount of time, so our split is also very well suited as a project light. Especially important in the object: we offer 5 years warranty on the function and vouch for the high quality workmanship and durability of this lamp.


2.500 lm	luminous flux [lm]
24,00 Watt	rated power
3000/4000 K	colour temperature
Ra>80	colour rendering
<5 sdcn	colour consistency
110°	beam angle

silber	Colour housing
IP54	type of protection
-10° - 40°C	temperature range in operation

0.95	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
24 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.5 s	starting time

Ø 30.000 h	nominal life time
L80B10	rated life time L70/B50
0.8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



ENERGY

SIGOR
4035001

A
B
C
D
E
F
G

24
kWh/1000h

2019/2015

as of: 20.03.2025

Page: 1



4035001

Aufbauleuchte Split 270mm silber



as of: 20.03.2025

Page: 2

Sigor Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal
Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61
info@sigor.de • www.sigor.de

Handelsregister HRB 19472
USt-IdNr.: DE 814574569
WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer:
Michael Perterer
Robin Scheffel

