

**Datasheet**  
**4043101**

**Panel Aufbau Fled 1200x300mm weiss UGR<22**


Our 36 W **FLED PANEL** surface-mount panel has a pre-installed frame and features a quick-mount system. With only 28 mm installation height and the Frame integrated driver, it corresponds to the appearance of an insert panel. It is suitable for schools, sports facilities and offices. Especially important in the object: we offer 5-year warranty and vouch for the high-quality workmanship and durability. The panel is equipped with the latest generation LED technology. This has increased the efficiency to 120 lm per watt. Power is supplied via an external driver which is included in the delivery program.



Dimmable no

4.320 lm	luminous flux [lm]
36,00 Watt	rated power
4000 K	colour temperature
Ra>80	colour rendering
<5 sdc	colour consistency
115°	beam angle
weiss	Colour housing
IP20	type of protection
-45° - 65°C	temperature range in operation
0.9	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
36 kWh/1000h	energy consumption
<1.0 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L70B10	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**SIGOR**  
4043101

A	
B	
C	
D	
E	← E
F	
G	


**36**  
kWh/1000h

2019/2015



4043101

Panel Aufbau Fled 1200x300mm weiss UGR<22



**Manual:**

[https://shop.sigor.de/media/pdf/4043101\\_manual.pdf](https://shop.sigor.de/media/pdf/4043101_manual.pdf)

as of: 11.09.2023

Page: 2

