

Datasheet

5114001

2W Luxar Glas MR11 36° GU4 200lm 2700K

Our 2W **LUXAR GLAS MR11** glass GU5.3 is optimally suited for object and design lamps due to the high-quality finish. It is equipped with the latest LED technology. Its color rendering with an RA value of 90 makes everything shine true to color.


The many variants of the module in light color and beam angles allow a wide coverage of the various fields of application. The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package of our LUXAR GLAS MR11 can be compared with a 20W conventional MR11.



Dimmable no

184 lm	luminous flux [lm]
2,30 Watt	rated power
20 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
6 sdcm	colour consistency
36°	beam angle
GU4	base
MR11	outer bulb
klar	type of glass
35 mm	length
35 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
	power factor
12 V AC	voltage
50/60 Hz	operating frequency
mA	current
3 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5114001

A	
B	
C	
D	
E	
F	← F
G	

2
kWh/1000h

2019/2015

as of: 28.11.2022

