



Datasheet

5280801

80W (100W) XENON R7S 78.0MM

Our 80W **HALOGEN FLUTLIGHT LAMP 78 mm** is the optimal illuminant for any floodlight. The rod can be operated in any burning position. In addition, the spiral suspension is designed to make the illuminant shockproof.


With an RA value of 99, all illuminated objects also look true to the original. The halogen rod has a perfect dimming range of 0-100%.




Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste

1.380 lm	luminous flux [lm]
80,00 Watt	rated power
100 Watt	equivalent incandescent lighting
2900 K	colour temperature
Ra>99	colour rendering
1 sdcm	colour consistency
360°	beam angle
R7s	base
QT-DE12	outer bulb
Klar	type of glass
78 mm	length
88 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
80 kWh/100h	energy consumption
<0,1 s	warm-up time up to 60% of the full light output
<0,1 s	starting time
Ø 2.000 h	nominal life time
L70B50	rated life time L70/B50
	lumen maintenance factor at the end of the nominal life





SIGOR
5280801

A

B

C

D


E

F

G

G

80
kWh/1000h



2019/2015

as of: 04.11.2021

