



Datasheet

5291201

120W (150W) XENON R7S 117.6MM

Unser 120W **HALOGEN FLUTLICHTLAMPE 117 mm** ist das optimale Leuchtmittel für jeden Flutlichtstrahler. Der Stab kann in jeder beliebigen Brennstellung betrieben werden. Zusätzlich ist die Wendelaufhängung so konzipiert, dass das Leuchtmittel stoßfest ist.

Mit einem RA-Wert von 99 sehen alle angestrahlten Objekte auch originalgetreu aus. Der Halogenstab weist eine perfekten Dimmbereich von 0-100% auf.




Dimmable: yes



Recommended dimmer: www.sigor.de/dimmerliste

2.250 lm	luminous flux [lm]
120,00 Watt	rated power
150 Watt	equivalent incandescent lighting
2900 K	colour temperature
Ra>99	colour rendering
1 sdcm	colour consistency
360°	beam angle
R7s	base
QT-DE12	outer bulb
Klar	type of glass
117 mm	length
9 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
120 kWh/100	energy consumption
<0,1 s	warm-up time up to 60% of the full light output
<0,1 s	starting time
Ø 2.000 h	nominal life time
L70B50	rated life time L70/B50
	lumen maintenance factor at the end of the nominal life





SIGOR
5291201

A

B

C

D

E

F

G

G

120
kWh/1000h



2019/2015

as of: 02.11.2021

