

**Datasheet**  
**5720201**

**6W Diled Modul 380lm 3000K 36° dim**




Dimmable: yes

Our 6W **Diled recessed module** is designed for the conversion of standard recessed luminaires. The shallow recessed depth of only 39mm also allows for use in cavity ceilings with limited space. The unique reflector perfectly imitates that of a halogen version. The high color rendering index of RA95 guarantees color rendering that is almost similar to daylight. The recessed module has a patented plastic lens that provides glare-free illumination. The lumen package of our Diled module can be compared with a 50W conventional GU10.

Recommended dimmer: [www.sigor.de/dimmerliste](http://www.sigor.de/dimmerliste)

380 lm	luminous flux [lm]
6,00 Watt	rated power
60 Watt	equivalent incandescent lighting
3000 K	colour temperature
Ra>95	colour rendering
<5 sdcn	colour consistency
36°	beam angle
Anschlussleitu	base
Modul	outer bulb
klar	type of glass
32 mm	length
50 mm	diameter
IP30	type of protection
-20° - 40°C	temperature range in operation
0,95	power factor
230 V AC	voltage
50/60 Hz	operating frequency
28 mA	current
6 kWh/1000h	energy consumption
<1.0 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0,8	lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**Sigor**  
5720201

A	
B	
C	
D	
E	
F	
G	G

**6**  
kWh/1000h

2019/2015

as of: 12.12.2024

