

Datasheet
5721201

9W Diled Modul 570lm 3000K 36° dim



Dimmable: yes


Our 9W **Diled recessed module** is designed for the conversion of standard recessed luminaires. The unique reflector perfectly imitates that of a halogen version. The high color rendering index of RA95 guarantees color rendering that is almost similar to daylight.


The recessed module has a patented plastic lens that provides glare-free illumination. The lumen package of our Diled module can be compared with a 75W conventional GU10.

Recommended dimmer: www.sigor.de/dimmerliste

570 lm	luminous flux [lm]
9,00 Watt	rated power
70 Watt	equivalent incandescent lighting
3000 K	colour temperature
Ra>95	colour rendering
<5 sdcms	colour consistency
36°	beam angle
Anschlussleitu	base
Modul	outer bulb
klar	type of glass
51 mm	length
50 mm	diameter
IP30	type of protection
-20° - 40°C	temperature range in operation
0.85	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
9 kWh/1000h	energy consumption
<1.0 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0,8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm





ENERGY

Sigor
5721201

A

B

C

D


E

F

G

G

8
kWh/1000h



2019/2015

as of: 09.10.2023

