

Datasheet
5721501

9W Diled Modul 580lm 3000K 60° dim




Dimmable: yes

Our 9W **Diled recessed module** is designed for the conversion of standard recessed luminaires. The unique reflector perfectly imitates that of a halogen version. The high color rendering index of RA95 guarantees color rendering that is almost similar to daylight. The recessed module has a patented plastic lens that provides glare-free illumination. The lumen package of our Diled module can be compared with a 70W conventional GU10.

Recommended dimmer: www.sigor.de/dimmerliste

580 lm	luminous flux [lm]
9,00 Watt	rated power
80 Watt	equivalent incandescent lighting
3000 K	colour temperature
Ra>95	colour rendering
<5 sdcM	colour consistency
60°	beam angle
Anschlussleitu Modul	base outer bulb type of glass
51 mm	length
50 mm	diameter
IP30	type of protection
-20° - 40°C	temperature range in operation
0.85	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
9 kWh/1000h	energy consumption
<1.0 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0,8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



Sigor
5721501

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	▶

G ◀

9
kWh/1000h

2019/2015

as of: 09.10.2023

