

Datasheet
5722101

Einbauleuchte Diled 5W 300lm 2700-2100K

Our 5W **Diled Downlight** is the successor of the successful Haled series from Sigor. The unique reflector perfectly imitates that of a halogen variant. Due to the high color rendering index, an almost daylight-like color rendering is guaranteed. The recessed downlight has the Dim-To-Warm technology. It is characterized by the lowering of the light color when dimming from 2,700K to 2,100K, as with a traditional incandescent lamp. The recessed luminaire is equipped with the latest LED technology and thus has high dimmer compatibility. The power supply is provided by an integrated driver. Especially important in the object: we offer 3-year warranty and vouch for the high-quality workmanship and durability.




Dimmable:

Recommended dimmer: www.sigor.de/dimmerliste

300 lm	luminous flux [lm]
5,00 Watt	rated power
2700-2100 K	colour temperature
Ra>95	colour rendering
<5 sdcms	colour consistency
36°	beam angle
schwarz	Colour housing
IP30	type of protection
-10° - 40°C	temperature range in operation
0.9	power factor
230 V AC	voltage
50/60 Hz	operating frequency
24 mA	current
4 kWh/1000h	energy consumption
<1.0 s	warm-up time up to 60% of the full light output
<0.5 s	starting time
Ø 50.000 h	nominal life time
L80B10	rated life time L70/B50
0,8	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5722101

A	
B	
C	
D	
E	
F	
G	G


5
kWh/1000h

2019/2015



5722101

Einbauleuchte Diled 5W 300lm 2700-2100K



Manual:

https://shop.sigor.de/media/pdf/5722101_manual.pdf

as of: 09.10.2023

Page: 2

SIGOR Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal
Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61
info@sigor.de • www.sigor.de

Handelsregister HRB 19472
USt-IdNr.: DE 814574569
WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer:
Michael Perterer
Robin Scheffel

