

Datasheet
5727901

Einbauleuchte 68 Diled Low Glare 6W 380lm 3000K



Dimmable yes


Our 6W **Downlights 68 Diled Low Glare** are characterized by a compact design with an ultra-flat installation depth of 49mm and direct connection to 230 V. Visually, they are almost indistinguishable from a halogen lamp. Thanks to the radiation via the reflector, the light is completely glare-free.

The recessed downlight has a brilliant light color of 2,700K and lets everything shine in a beautiful light. In a white die-cast housing, our Diled sets its accents. The recessed luminaire is equipped with the latest LED technology and is therefore highly dimmer-compatible. Power is supplied via an integrated driver.

Recommended dimmer: www.sigor.de/dimmerliste

| | |
|-------------|---|
| 350 lm | luminous flux [lm] |
| 6,00 Watt | rated power |
| 3000 K | colour temperature |
| Ra>95 | colour rendering |
| <5 sdcn | colour consistency |
| 32° | beam angle |
| weiß | Colour housing |
| IP20 | type of protection |
| -20° - 40°C | temperature range in operation |
| 0.9 | power factor |
| 230 V AC | voltage |
| 50/60 Hz | operating frequency |
| 28 mA | current |
| 6 kWh/1000h | energy consumption |
| <1.0 s | warm-up time up to 60% of the full light output |
| <0.5 s | starting time |
| Ø 40.000 h | nominal life time |
| L70B50 | rated life time L70/B50 |
| 0.7 | lumen maintenance factor at the end of the nominal life |

Spectral power distribution in the range 180 - 800 nm



Sigor
5727901

| | |
|---|---|
| A | |
| B | |
| C | |
| D | |
| E | |
| F | |
| G | G |

6
kWh/1000h

2019/2015

as of: 28.03.2024

