

Datasheet 5732201

5W Diled 90 GU10 Ra90 350lm 3000K 36° dim



Our 5W Diled GU10 90 is the successor to the successful Haled series from Sigor. The unique reflector perfectly imitates that of a halogen variant. The reflector can be tilted up to 50 °. Due to the high color rendering index, an almost daylight-like color rendering is guaranteed.

The recessed downlight has a brilliant light color of 3,000K and makes everything shine in a beautiful light. The GU10 is equipped with the latest LED technology and thus has a high dimmer compatibility.



Recommended dimmer: www.sigor.de/dimmerliste

360 lm luminous flux [lm] 5,00 Watt rated power

60 Watt equivalent incandescent lighting

3000 K colour temperature Ra>90 colour rendering <5 sdcm colour consistency 36°

beam angle

GU10 base PAR16 outer bulb

type of glass

60 mm length 50 mm diameter

IP20 type of protection

-10° - 30°C temperature range in operation

power factor

230 V AC voltage

50/60 Hz operating frequency

16 mA current

5 kWh/1000h energy consumption

warm-up time up to 60% of the full light output <1,0 s

<0.5 s starting time

Ø 25.000 h nominal life time rated life time L70/B50 L70B50

lumen maintenance factor at the end of the 0.7

Handelsregister HRB 19472


WEEE-Reg.-Nr.: DE 45242363

DE 814574569

USt-IdNr.:

nominal life

Spectral power distribution in the range 180 - 800 nm













Geschäftsführer:

Michael Perterer

Robin Scheffel



as of: 05.09.2023