

Datasheet
5750901

2,6W ECOLUX GY6,35 300lm 2700K


Our 2.6W **ECOLUX GY6.35** plug-in base lamp is due to your small dimensions perfectly suited for use in confined spaces. It is equipped with the most modern LED technology and thus has a long service life. The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package our GY6.35 can be compared with a 28W conventional GY6.35.



Dimmable no

300 lm	luminous flux [lm]
2,60 Watt	rated power
28 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcms	colour consistency
320°	beam angle
GY6,35	base
QT12-ax	outer bulb
klar	type of glass
40 mm	length
14 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0.5	power factor
12 V AC	voltage
50/60 Hz	operating frequency
350 mA	current
3 kWh/1000h	energy consumption
<1,0 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5750901

A	
B	
C	
D	
E	
F	← F
G	

3
kWh/1000h

2019/2015

as of: 29.11.2022

