

Menschen im Licht.

Datasheet 5752901

7.4W Luxar Glas GU10 460Im 2700K 36° dim

G d


Our 7.4W LUXAR GLAS PAR16 is optimally suited for object and design lights due to the high quality finish. It is equipped with the latest LED technology and thus has a high dimmer compatibility. Its color rendering with an RA value of 90 makes everything shine true to color. The many variants of the module in light color and beam angles allow a wide coverage of different fields of application. The low power consumption of the LED is confirmed by the good energy efficiency class.



Recommended dimmer: www.sigor.de/dimmerliste

	-	
460 lm 7,40 Watt	luminous flux [lm] rated power	Spectral power distribution in the range 180 - 800 nm
65 Watt	equivalent incandescent lighting	-
2700 K	colour temperature	
Ra>90 <6 sdcm	colour rendering colour consistency	
36°	beam angle	40
		40 /V
GU10	base	
QPAR51	outer bulb	
klar 54 mm	type of glass length	T
50 mm	diameter	<u>/</u> ,
IP	type of protection	
-20° - 40°C	temperature range in operation	$(\in $
0.7	power factor	
220-240 V AC	•	
50/60 Hz	operating frequency	ENER
35 mA	current	
8 kWh/1000h <1.0 s	energy consumption warm-up time up to 60% of the full light output	SIGOR
<0.5 s	starting time	5752901
0.00		
Ø 25.000 h	nominal life time	A
L70B50	rated life time L70/B50	B
0.7	lumen maintenance factor at the end of the nominal life	





as of: 24.01.2024

SIGOR Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal Handelsregister HRB 19472 Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61 info@sigor.de • www.sigor.de

USt-IdNr.: DE 814574569 WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer: Michael Perterer Robin Scheffel