

Datasheet
5753201

2W Ecolux G9 220lm 2700K

Our 2W **ECOLUX G9** plug-in base lamp is due to your small dimensions perfectly suited for use in confined spaces. It is equipped with the latest LED technology.


The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package our G9 can be compared with a 22W conventional G9



Dimmable no

220 lm	luminous flux [lm]
2,00 Watt	rated power
22 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcM	colour consistency
320°	beam angle
G9	base
QT14	outer bulb
klar	type of glass
51 mm	length
15 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0,7	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
2 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5753201

A	
B	
C	
D	
E	←
F	
G	

2
kWh/1000h

2019/2015

as of: 28.11.2022

