

Datasheet
5753301

3,2W Ecolux G9 400lm 2700K

Our 3.2W **ECOLUX G9** plug-in base lamp is perfectly suited for use in confined spaces due to your small dimensions. It is equipped with the latest LED technology.


The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package our G9 can be compared with a 35W conventional G9.



Dimmable no

400 lm	luminous flux [lm]
3,20 Watt	rated power
35 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcms	colour consistency
320°	beam angle
G9	base
QT14	outer bulb
klar	type of glass
57 mm	length
17 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0,7	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
4 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5753301

A	
B	
C	
D	
E	← E
F	
G	

3
kWh/1000h

2019/2015

as of: 28.11.2022

