

Datasheet
5754201

1,5W Ecolux G4 180lm 2700K

Our 1.5W **ECOLUX G4** plug-in base lamp acquires its small dimensions through the filament technology used and is thus perfectly suited for use in confined spaces. Furthermore, the filament provides a shapely illumination. It is equipped with the latest LED technology and thus has a long service life.


The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package our G4 can be compared with a 19W conventional G4.



Dimmable no

180 lm	luminous flux [lm]
1,50 Watt	rated power
19 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcms	colour consistency
320°	beam angle
G4	base
QT9-ax	outer bulb
klar	type of glass
40 mm	length
14 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0,7	power factor
12 V AC	voltage
50/60 Hz	operating frequency
mA	current
2 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5754201

A	
B	
C	
D	
E	←
F	
G	

2
kWh/1000h

2019/2015

as of: 29.11.2022

