

Datasheet
5755301

7W Luxar R7s Slim 78mm 806lm 2700K

Our 7W **LUXAR R7s SLIM** rod is the perfect replacement for the classic halogen rods. The slim design of 20mm diameter also allows the use in confined spaces.


The R7S rod is equipped with the latest LED technology and thus has a long service life. The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package our R7s can be compared with a 60W conventional R7s.



Dimmable no

806 lm	luminous flux [lm]
7,00 Watt	rated power
60 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcms	colour consistency
360°	beam angle
R7s	base
QT-DE12	outer bulb
klar	type of glass
78 mm	length
20 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0,7	power factor
230 V AC	voltage
50/60 Hz	operating frequency
mA	current
7 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 15.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5753301

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	▶

4
kWh/1000h

2019/2015

as of: 29.11.2022

