

Datasheet

5758201

Dimmable:yes

9W Ecolux B15d 1055lm 2700K Dim

Our 9W ECOLUX B15d is the new family member in our Ecolux family. It expands the group with its powerful LEDs on a B15d base. Due to the compact design He can be easily integrated into many design luminaires.

It is equipped with the latest LED technology and thus has a high dimmer compatibility. The low power consumption of the LED is confirmed by the good energy efficiency class.

If you would like to know with which dimmers this product is compatible, please follow the link to the test results from our own workshop.

Recommended dimmer: www.sigor.de/dimmerliste

1.055 lm luminous flux [lm] 9,00 Watt rated power

75 Watt equivalent incandescent lighting

2700 K colour temperature Ra>80 colour rendering <6 sdcm colour consistency 320°

beam angle

B15d base **QT18** outer bulb klar type of glass length 101 mm 18 mm diameter

IP20 type of protection

-20° - 40°C temperature range in operation

power factor 0,5 230 V AC voltage

50/60 Hz operating frequency

50 mA current

9 kWh/1000h energy consumption

warm-up time up to 60% of the full light output <1,0 s

<0,5 s starting time


Ø 15.000 h nominal life time L70B50 rated life time L70/B50

lumen maintenance factor at the end of the 0.7

USt-IdNr.:


nominal life

Spectral power distribution in the range 180 - 800 nm











Geschäftsführer:

Michael Perterer

Robin Scheffel

DE 814574569

WEEE-Reg.-Nr.: DE 45242363

as of: 24.11.2022