

Datasheet 5759101

4W ECOLUX G9 470lm 2700K dim

Our 4W **ECOLUX G9** plug-in base lamp is due to your small dimensions perfectly suited for use in confined spaces. It is equipped with the latest LED technology and thus has a high dimmer compatibility. The low power consumption of the LED is confirmed by the good energy efficiency class.



Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste


470 lm	luminous flux [lm]
4,00 Watt	rated power
40 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcn	colour consistency
320°	beam angle

G9	base
QT14	outer bulb
klar	type of glass
59 mm	length
18 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation

0.5	power factor
230 V AC	voltage
50/60 Hz	operating frequency
24 mA	current
4 kWh/1000h	energy consumption
<1,0 s	warm-up time up to 60% of the full light output
<0,5 s	starting time

Ø 25.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



ENERGY

SIGOR
5759101

A
B
C
D
E
F
G

4
kWh/1000h

2019/2015

as of: 28.11.2022