

Datasheet
5759201

3,2W ECOLUX G9 350lm 2700K dim

Our 3.2W **ECOLUX G9** plug-in base lamp is due to your small dimensions perfectly suited for use in confined spaces. It is equipped with the latest LED technology and thus has a high dimmer compatibility. The low power consumption of the LED is confirmed by the good energy efficiency class.




Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste

| | |
|--------------|---|
| 350 lm | luminous flux [lm] |
| 3,20 Watt | rated power |
| 32 Watt | equivalent incandescent lighting |
| 2700 K | colour temperature |
| Ra>80 | colour rendering |
| <6 sdcms | colour consistency |
| 320° | beam angle |
| G9 | base |
| QT14 | outer bulb |
| klar | type of glass |
| 59 mm | length |
| 18 mm | diameter |
| IP20 | type of protection |
| -20° - 40°C | temperature range in operation |
| 0.5 | power factor |
| 220-240 V AC | voltage |
| 50/60 Hz | operating frequency |
| 18 mA | current |
| 4 kWh/1000h | energy consumption |
| <1.0 s | warm-up time up to 60% of the full light output |
| <0.5 s | starting time |
| Ø 15.000 h | nominal life time |
| L70B50 | rated life time L70/B50 |
| 0.7 | lumen maintenance factor at the end of the nominal life |

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5759201

| | |
|---|-----|
| A | |
| B | |
| C | |
| D | |
| E | |
| F | ← F |
| G | |

4
kWh/1000h

2019/2015

as of: 04.12.2023

