Menschen im Licht

230 lm

50 mm IP20

° - °C



Datasheet 5777101

3,5W R50 Ecolux E14 230Im 2700K dim

Honey, salt and discontinued light sources have one thing in common: they don't go bad. Often it's small changes to the design or lumen package, or even just a switch to a different production center, that causes a bulb, fixture, or the like to no longer be carried over into a new product line. But that doesn't make them bad. For foxes, who are on the thing after a good bargain, offers our Abverkaufsware neat fodder - and without risk, because our guarantee applies to this just as for current catalog goods!



luminous flux [lm] 3,50 Watt rated power 40 Watt equivalent incandescent lighting 2700 Κ colour temperature Ra>80 colour rendering colour consistency sdcm 36° beam angle E14 base R50 outer bulb KLAR type of glass 84 mm length

type of protection

diameter

Recommended dimmer: www.sigor.de/dimmerliste



230 V AC Hz 20 mA 4 kWh/1000 <1 s <0.5 s	power factor voltage operating frequency current energy consumption warm-up time up to 60% of the full light output starting time
Ø 15.000 h	nominal life time rated life time L70/B50 lumen maintenance factor at the end of the nominal life

temperature range in operation

as of: 01.02.2022

USt-IdNr.: DE 814574569 WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer: Michael Perterer Robin Scheffel

