

Menschen im Licht.

Datasheet 5785801

A † G G

15,2W Luxar Glas PAR38 E27 1035lm 2700K IP65 dim

Our 15.2W LUXAR PAR38 OUTDOOR IP65 is optimally suited for outdoor applications due to its high-quality design. Its high-quality glass reflector makes a noble impression in any ground spike spotlight. It is equipped with the latest LED technology and thus has a high dimmer compatibility. The low power consumption of the LED is confirmed by the good energy efficiency class. If you would like to know with which dimmers this product is compatible, please follow the link to the test results from our own workshop.



Recommended dimmer: www.sigor.de/dimmerliste

1.035 lm 15,20 Watt 120 Watt 2700 K Ra>90 <6 sdcm 30°	luminous flux [lm] rated power equivalent incandescent lighting colour temperature colour rendering colour consistency beam angle	Spectral power distribution in the range 180 - 800 nm
E27 PAR38 matt 134 mm 122 mm IP65 -20° - 40°C	base outer bulb type of glass length diameter type of protection temperature range in operation	
0.7 230 V AC 50/60 Hz 91 mA 16 kWh/1000h <1,0 s <0,5 s	power factor voltage operating frequency current energy consumption warm-up time up to 60% of the full light output starting time	ENERO SIGOR 5785801
Ø 15.000 h L70B50 0.7	nominal life time rated life time L70/B50 lumen maintenance factor at the end of the nominal life	A B C



as of: 24.11.2022

SIGOR Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal Handelsregister HRB 19472 Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61 info@sigor.de • www.sigor.de

USt-IdNr.: WEEE-Reg.-Nr.: DE 45242363

DE 814574569

Geschäftsführer: Michael Perterer Robin Scheffel

