

**Datasheet**  
**5793701**

**9W Argent Modul 685lm 4000K 36° dim**




Dimmable: yes

Our 9W **Argent recessed module** is designed for the conversion of standard recessed luminaires. The high color rendering index of RA>90 withstands the highest demands on the light. Due to the optimal thermal management, a very long service life can be achieved. The many variants of the module in light color and beam angles allow a wide coverage of different fields of application.

Recommended dimmer: [www.sigor.de/dimmerliste](http://www.sigor.de/dimmerliste)

685 lm	luminous flux [lm]
9,00 Watt	rated power
75 Watt	equivalent incandescent lighting
4000 K	colour temperature
Ra>90	colour rendering
<6 sdcm	colour consistency
36°	beam angle
Anschlussleitu	base
Modul	outer bulb
klar	type of glass
50 mm	length
50 mm	diameter
IP20	type of protection
-10° - 40°C	temperature range in operation
0.85	power factor
230 V AC	voltage
50/60 Hz	operating frequency
450 mA	current
9 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.1 s	starting time
Ø 50.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**SIGOR**  
5793701

A	
B	
C	
D	
E	
F	← F
G	

9 kWh/1000h

2019/2015

as of: 25.11.2022

