

Datasheet
5797601

5,5W Argent Modul 384lm 3000K 24° dim

Our 5,5W **Argent recessed module** is designed for the conversion of standard recessed luminaires. The shallow recessed depth of only 37mm also allows for use in cavity ceilings with limited space. The high color rendering index of RA>95 withstands the highest demands on light. Due to the optimal thermal management a very long lifetime can be achieved. The many variants of the module in light color and beam angles allow a wide coverage of different fields of application.



Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste


384 lm	luminous flux [lm]
5,50 Watt	rated power
50 Watt	equivalent incandescent lighting
3000 K	colour temperature
Ra>95	colour rendering
<6 sdcms	colour consistency
24°	beam angle

Anschlussleitu	base
Modul	outer bulb
klar	type of glass
37 mm	length
50 mm	diameter
IP20	type of protection
-10° - 40°C	temperature range in operation

0,78	power factor
230 V AC	voltage
50/60 Hz	operating frequency
300 mA	current
6 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.1 s	starting time

Ø 50.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5797601

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	▶

6 kWh/1000h

2019/2015

as of: 25.11.2022

