

Datasheet
5798001

5,5W Argent Modul 379lm 3000K 36° dim

Our 6W Argent recessed module is designed for the conversion of standard recessed luminaires. The small installation depth of only 37mm also allows the use in cavity ceilings with limited space.

The high color rendering index of RA>95 withstands the highest demands on the light. Due to the optimal thermal management, a very long service life can be achieved. The many variants of the module in light color and beam angles allow a wide coverage of the various fields of application.



Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste


379 lm	luminous flux [lm]
5,50 Watt	rated power
50 Watt	equivalent incandescent lighting
3000 K	colour temperature
Ra>95	colour rendering
<6 sdcms	colour consistency
36°	beam angle

Anschlussleitu	base
Modul	outer bulb
klar	type of glass
37 mm	length
50 mm	diameter
IP20	type of protection
-10° - 40°C	temperature range in operation

0,78	power factor
230 V AC	voltage
50/60 Hz	operating frequency
300 mA	current
6 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.1 s	starting time

Ø 50.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5798001

A	
B	
C	
D	
E	
F	
G	G

6
kWh/1000h

2019/2015

as of: 25.11.2022

