

## Datasheet

5834101

### 22W Tube INSTANT-PRO G13 1500mm 3300lm 4000K


Our 22W LED Tube **INSTANT-PRO TUBE** is the optimal replacement for the classic fluorescent tube with a magnetic ballast (KVG/MVG). The required starter is included in the delivery.



Dimmable no

3.300 lm	luminous flux [lm]
22,00 Watt	rated power
58 Watt	equivalent incandescent lighting
4000 K	colour temperature
Ra>80	colour rendering
<6 sdcms	colour consistency
160°	beam angle
G13	base
T8	outer bulb
opal	type of glass
15.142 mm	length
28 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0.92	power factor
230 V AC	voltage
50/60 Hz	operating frequency
0.12 mA	current
22 kWh/1000h	energy consumption
<0,5 s	warm-up time up to 60% of the full light output
<0,5 s	starting time
Ø 25.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**SIGOR**  
5834101

A	
B	
C	
D	D
E	
F	
G	

**22**  
kWh/1000h

2019/2015

as of: 29.11.2022

