SIG

Menschen im Licht.

Datasheet 5911401


11W/m ART OMNI LED-Streifen 3000K 10m

Our 10W ART OMNI STREIFEN IP67 can also be used directly in the visible range due to its three-sided light emission without recognizable light points. By the homogeneous light distribution without recognizable light points as well as the high-quality, satin polyurethane casting He needs no more cover on the profile. Heat dissipation is already provided by the PU potting and an aluminum or acrylic rail is used for mounting or guiding. The material is insensitive to acids and alkalis, so the strip can be used without hesitation in adverse environments such on ships (salt water) or in kitchens (wipe with detergents). The power outlet of the strip is located at the bottom. This has the advantage that a perfect transition, without shadow gap, of two strips is possible. Thus, the feed can be hidden quite inconspicuously in the light object.



		844.8 1.1	9-m-11-10-00-0
8.400 lm	luminous flux		
840 lm/m	luminous flux / m		
100 Watt	rated power	••	
11 Watt/m	rated power / m	M 1	
24 V DC	output voltage	* beg	W River
3000 K	colour temperature		
Warmweiss	colour perception		
Ra>90	colour rendering		
<5 sdcm 120°	colour consistency	1	
120	beam angle		
10.000 mm	length of strip on wheel		
10.000 mm	max. strip length		
13 mm	width		
12 mm	height		
COB	LED chipset	CE	
156 LED/m	LED chips / m		-
0 mm	LED pitch	1000	NEF
385 mm 1000 mm	smallest cuttable unit length connection cable side 1	Sec. 1	INE
1000 mm	length connection cable side 2	GTCOD	
120 mm	lowest bending radius	SIGOR	
IP67	type of protection	5911401	
1 07			
60 °C	max. temperature at tc test point	A	
-25° - 55°C	temperature range in operation	B	
no	Aluminum profile necessary for cooling?	в	
Ø 36.000 h	nominal life time	C	
L70B10	rated life time		
0.7	lumen maintenance factor at the end of the nominal life	D	
460 mA	nominal current	E	
55 kWh/1000h	energy consumption		
		it.	

Spectral power distribution in the range 180 - 800 nm





028085

5911

as of: 12.09.2023

USt-IdNr.: WEEE-Reg.-Nr.: DE 45242363

DE 814574569

Geschäftsführer: Michael Perterer Robin Scheffel





5911401

11W/m ART OMNI LED-Streifen 3000K 10m



https://shop.sigor.de/media/pdf/5911401_manual.pdf

as of: 12.09.2023 Page: 2

SIGOR Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal Handelsregister HRB 19472 Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61 info@sigor.de • www.sigor.de

USt-IdNr.: DE 814574569 WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer: Michael Perterer Robin Scheffel

