

**Datasheet**  
**5935301**

**21,6W/m PRO LED-Streifen 4000K 5m**

Our 21.6 W **PRO STRIP IP20** belongs to the most frequently used strip group in the upscale lighting object. Here you have access to a wide range of luminous intensities and light colors from 2,700 K to 4,000 K.



A tight binning with only 3 SDCM guarantees a homogeneous light color both on the strip and with different strips of this type.


Especially important in the object: we offer a 5-year warranty and vouch for the high-quality workmanship and durability of these strips.



Dimmable yes

14.820 lm	luminous flux
3.461 lm/m	luminous flux / m
108 Watt	rated power
21.60 Watt/m	rated power / m
24 V DC	output voltage
4000 K	colour temperature
Neutralweiss	colour perception
Ra>90	colour rendering
<3 sdcn	colour consistency
120°	beam angle
5.000 mm	length of strip on wheel
3.500 mm	max. strip length
10 mm	width
1.65 mm	height
2835	LED chipset
240 LED/m	LED chips / m
4.16 mm	LED pitch
33.33 mm	smallest cuttable unit
1000 mm	length connection cable side 1
1000 mm	length connection cable side 2
25 mm	lowest bending radius
IP20	type of protection
80 °C	max. temperature at tc test point
-40° - 85°C	temperature range in operation
yes	Aluminum profile necessary for cooling?
Ø 54.000 h	nominal life time
L70B50	rated life time
0.7	lumen maintenance factor at the end of the nominal life
1	power factor
900 mA	nominal current
108 kWh/1000	energy consumption

Spectral power distribution  
in the range 180 - 800 nm



**SIGOR**  
5935301

A	
B	
C	
D	D
E	
F	
G	

**108**  
kWh/1000h

2019/2015

as of: 05.12.2023



5935301

21,6W/m PRO LED-Streifen 4000K 5m



**Manual:**

[https://shop.sigor.de/media/pdf/5935301\\_manual.pdf](https://shop.sigor.de/media/pdf/5935301_manual.pdf)

as of: 05.12.2023

Page: 2

