

**Datasheet**  
**5946001**

**6W Stablampe opal S14s 300mm 600lm 2700K**

Our 6W **STABLAMPEN OPAL** is the perfect replacement for the classic Linestra line lamp. The illuminant is equipped with the latest LED technology and thus has a long service life.


Furthermore, the use of the technology guarantees flicker-free operation. The illuminant has an opalized glass for a shadow-free illumination. The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package of our STABLAMPEN can be compared with a 48W conventional Linestra.



Dimmable no

600 lm	luminous flux [lm]
6,00 Watt	rated power
48 Watt	equivalent incandescent lighting
2700 K	colour temperature
Ra>80	colour rendering
<6 sdcm	colour consistency
270°	beam angle
S14s	base
L-DE	outer bulb
opal	type of glass
300 mm	length
30 mm	diameter
IP20	type of protection
-20° - 40°C	temperature range in operation
0.52	power factor
230 V AC	voltage
50/60 Hz	operating frequency
50 mA	current
6 kWh/1000h	energy consumption
<0,3 s	warm-up time up to 60% of the full light output
<0,1 s	starting time
Ø 25.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution  
in the range 180 - 800 nm



**SIGOR**  
5946001

A	
B	
C	
D	
E	
F	← F
G	

**6**  
kWh/1000h

2019/2015

as of: 29.11.2022

