SIG

Menschen im Licht.

Datasheet 5946401

16W Stablampe opal S14s 1000mm 1600lm 2700K

Our 16W STABLAMPEN OPAL is the perfect replacement for the classic Linestra line lamp. The illuminant is equipped with the latest LED technology and thus has a long service life.

Furthermore, the use of the technology guarantees flicker-free operation. The illuminant has an opalized glass for a shadow-free illumination. The low power consumption of the LED is confirmed by the good energy efficiency class. The lumen package of our STABLAMPEN can be compared with a 48W conventional Linestra.





1.600 lm 16,00 Watt 105 Watt 2700 K Ra>80 <6 sdcm 270°	luminous flux [Im] rated power equivalent incandescent lighting colour temperature colour rendering colour consistency beam angle	Spectral power distribution in the range 180 - 800 nm
S14s L-DE opal 1.000 mm 30 mm IP20 -20° - 40°C	base outer bulb type of glass length diameter type of protection temperature range in operation	
0.75 230 V AC 50/60 Hz 85 mA 16 kWh/1000h <0,3 s <0,1 s	power factor voltage operating frequency current energy consumption warm-up time up to 60% of the full light output starting time	SIGOR 5946401
Ø 25.000 h L70B50 0.7	nominal life time rated life time L70/B50 lumen maintenance factor at the end of the nominal life	A B C



as of: 29.11.2022

SIGOR Licht GmbH • Eichenhofer Weg 81 • 42279 Wuppertal Handelsregister HRB 19472 Telefon 0 23 39 - 12 61 - 0 • Telefax 0 23 39 - 12 61 61 info@sigor.de • www.sigor.de

USt-IdNr.: DE 814574569 WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer: Michael Perterer Robin Scheffel

028085

594