

Datasheet
5957201

10W/m COB mini cut LED-Streifen 2700K 5m

Our 10W **COB mini cut LED STRIP** emits homogeneous light without any light spots at all. Therefore, it is particularly well suited for use in very flat profiles or indirect lighting with a short distance to reflective surfaces. This is made possible by the continuous phosphor coating.




The high separability of the LED strip makes it possible to install it with almost perfect fit.



Dimmable: yes

3.550 lm	luminous flux
650 lm/m	luminous flux / m
50 Watt	rated power
10 Watt/m	rated power / m
24 V DC	output voltage
2700 K	colour temperature
Warmweiss	colour perception
Ra>90	colour rendering
3 sdcm	colour consistency
180°	beam angle
5.000 mm	length of strip on wheel
5.000 mm	max. strip length
8 mm	width
18 mm	height
COB	LED chipset
528 LED/m	LED chips / m
189 mm	LED pitch
1.136 mm	smallest cuttable unit
1000 mm	length connection cable side 1
1000 mm	length connection cable side 2
50 mm	lowest bending radius
IP20	type of protection
65 °C	max. temperature at tc test point
-20° - 60°C	temperature range in operation
no	Aluminum profile necessary for cooling?
Ø 54.000 h	nominal life time
L80B10	rated life time
0,98	lumen maintenance factor at the end of the nominal life
428 mA	nominal current
50 kWh/1000h	energy consumption

Spectral power distribution
in the range 180 - 800 nm



Sigor
5957201

A
B
C
D
E
F
G

G

50
kWh/1000h

2019/2015

as of: 15.08.2023

