

Datasheet
5959501

10,85W/m HE PRO LED-Streifen 3000K 5m


Our 7.5 W **PRO HE STRIP IP20** is all about protecting the environment. Compared to our conventional LED strips, the HE strip is 30% more efficient. It has a remarkable efficiency of 180 lm/W. By using smaller power supplies, a very environmentally friendly lighting solution can be created. A narrow binning with only 3 SDCM guarantees a homogeneous light colour on the strip as well as on different strips of this type. Particularly important in the project: we offer a 5-year guarantee and vouch for the high-quality workmanship and durability of these strips. For easier installation and further processing, we have provided the strip with a feed and a secondary feed of 1 metre each.



Dimmable yes

10.030 lm	luminous flux
2.006 lm/m	luminous flux / m
54.25 Watt	rated power
10.85 Watt/m	rated power / m
24 V DC	output voltage
3000 K	colour temperature
Warmweiss	colour perception
Ra>90	colour rendering
<3 sdcM	colour consistency
120°	beam angle
5.000 mm	length of strip on wheel
5.000 mm	max. strip length
10 mm	width
1.50 mm	height
2835	LED chipset
234 LED/m	LED chips / m
4.27 mm	LED pitch
38.46 mm	smallest cuttable unit
1000 mm	length connection cable side 1
1000 mm	length connection cable side 2
50 mm	lowest bending radius
IP20	type of protection
80 °C	max. temperature at tc test point
-40° - 80°C	temperature range in operation
no	Aluminum profile necessary for cooling?
Ø 54.000 h	nominal life time
L80B10	rated life time
0.8	lumen maintenance factor at the end of the nominal life
452 mA	nominal current
55 kWh/1000h	energy consumption

Spectral power distribution
in the range 180 - 800 nm



SIGOR
5959501

A	
B	
C	← C
D	
E	
F	
G	

55
kWh/1000h

2019/2015

as of: 05.12.2023



5959501

10,85W/m HE PRO LED-Streifen 3000K 5m



Manual:

https://shop.sigor.de/media/pdf/5959501_manual.pdf

as of: 05.12.2023

Page: 2

