

Datasheet 6140801

4,5W Kerze Filament opal E14 470lm 2700K dim



Dimmable: yes


Our 4.5W filament candle lamp is the optimal replacement for traditional incandescent lamps due to its classic look. It is equipped with the latest 5th generation filament technology and thus has a high dimmer compatibility. Its color rendering with an RA value of 90 makes everything shine with true colors. The low power consumption of the filament is confirmed by the good energy efficiency class. The illuminant has an opalized glass for a shadow-free illumination.

If you would like to know with which dimmers this product is compatible, please follow the link to the test results from our own workshop.

Recommended dimmer: www.sigor.de/dimmerliste

| | |
|-------------|---------------------------------------------------------|
| 470 lm | luminous flux [lm] |
| 4,50 Watt | rated power |
| 40 Watt | equivalent incandescent lighting |
| 2700 K | colour temperature |
| Ra>90 | colour rendering |
| <6 sdcms | colour consistency |
| 300° | beam angle |
| E14 | base |
| C35 | outer bulb |
| opal | type of glass |
| 97 mm | length |
| 35 mm | diameter |
| IP20 | type of protection |
| -20° - 40°C | temperature range in operation |
| 0.7 | power factor |
| 230 V AC | voltage |
| 50/60 Hz | operating frequency |
| 26 mA | current |
| 5 kWh/1000h | energy consumption |
| <0.5 s | warm-up time up to 60% of the full light output |
| <0.5 s | starting time |
| Ø 15.000 h | nominal life time |
| L70B50 | rated life time L70/B50 |
| 0.7 | lumen maintenance factor at the end of the nominal life |

Spectral power distribution
in the range 180 - 800 nm



SIGOR
6140801

| | |
|---|-----|
| A | |
| B | |
| C | |
| D | |
| E | |
| F | ← F |
| G | |

5
kWh/1000h

2019/2015

as of: 23.11.2022

