

Datasheet 9200201

Netzteil POWERLINE BASE 60W 24VDC




Our 60W **POWERLINE BASE** in 24V finds its application in the power supply of LED strips. The article group of POWERLINE BASE stands for a good price-performance ratio. It has IP20 protection and is therefore not suitable for outdoor use. The minimum load of the power supply is 10% of the total power. Our power supply is protected against short circuit, overload and overvoltage. Our power supply is considered EMC interference resistant, which means that our power supply will not disturb other devices by unwanted electrical or electromagnetic effects or be disturbed by other devices.

Especially important in the object: we offer 3 years warranty and vouch for the high quality workmanship and durability of this power supply.



| | |
|-----------|----------------------------|
| 230 V | AC Voltage |
| 50/60 Hz | Frequency Range |
| 100-265 V | Voltage Range AC |
| 24-25,2 V | Voltage Range DC |
| mA | AC Current |
| 60,00 W | Rated Power |
| % | Full Load Efficiency |
| 96,00 | Power Factor |
| 0,90 W | Power at Standby |
| | Inrush Current |
| | Dimming method |
| keine Hz | Radio frequency |
| 0 kHz | PWM-frequency |
| 24 V | Output voltage |
| 1 % | Voltage Tolerance |
| 60 W | Output Power |
| 2,5 A | Output Current |
| -- mA | Constant Current range |
| 70 °C | Ambient Temperature |
| 80 °C | Storage Temperature |
| 80 °C | Max. Housing Temp. |
| IP20 | Ingress Protection Code |
| 2 | Protection Class |
| 0 % | Total Harmonic distortion |
| L70B50 h | Calculated Lifetime |
| 20000 h | Lifetime |
| 3 a | Guarantee |
| 180 mm | Dimensions |
| 52 mm | width |
| 30 mm | height |
| g | Weight |
| Ja | Shortcircuit proof |
| Nein | Overtemperature protection |
| Nein | Overvoltage Protection |
| 100000 | Switching cycles |



as of: 19.09.2023

