SIG

Menschen im Licht.

Datasheet 9200301




Netzteil POWERLINE BASE 75W 24VDC

Our 75W POWERLINE BASE in 24V finds its application in the power supply of LED strips. The article group of POWERLINE BASE stands for a good price-performance ratio. It has IP20 protection and is therefore not suitable for outdoor use. The minimum load of the power supply is 10% of the total power. Our power supply is protected against short circuit, overload and overvoltage. Our power supply is considered EMC interference resistant, which means that our power supply will not disturb other devices by unwanted electrical or electromagnetic effects or be disturbed by other devices.

Especially important in the object: we offer 3 years warranty and vouch for the high quality workmanship and durability of this power supply.



230 V 50/60 Hz 100-265 V 24-25,2 V mA 75,00 W % 96,00 0,90 W	AC Voltage Frequency Range Voltage Range AC Voltage Range DC AC Current Rated Power Full Load Efficiency Power Factor Power at Standby Inrush Current
keine Hz 0 kHz 24 V 1 % 75 W 3,13 A mA 70 °C 80 °C IP20 2 0 % h 20000 h 3 a 180 mm 52 mm 30 mm 9 Ja Nein Nein 100000	Dimming method Radio frequency PWM-frequency Output voltage Voltage Tolerance Output Power Output Current Constant Current range Ambient Temperature Storage Temperature Max. Housing Temp. Ingress Protection Code Protection Class Total Harmonic distortion Calculated Lifetime Lifetime Guarantee Dimensions width height Weight Shortcircuit proof Overtemperature protection Overvoltage Protection



as of: 19.09.2023

USt-IdNr.: DE 814574569 WEEE-Reg.-Nr.: DE 45242363

Geschäftsführer: Michael Perterer Robin Scheffel

