


Datasheet
9205102

Netzteil Powerline Panel CC 36W

Unser **Powerline Konstantstromtreiber** wird von Philips gefertigt und sorgt für die Stromversorgung des Fled Backlit Panels. Der Treiber ist ENEC zertifiziert und sorgt für eine flickerfreie Ausleuchtung. Die angeschlossenen Leitungen minimieren den Installationsaufwand.



230 V	AC Voltage
50/60 Hz	Frequency Range
220-240 V	Voltage Range AC
30-40 V	Voltage Range DC
900,00 mA	AC Current
41,00 W	Rated Power
89,00 %	Full Load Efficiency
0,95	Power Factor
0,50 W	Power at Standby
14,7A;155u	Inrush Current
	Dimming method
keine Hz	Radio frequency
0 kHz	PWM-frequency
40 V	Output voltage
0 %	Voltage Tolerance
36 W	Output Power
A	Output Current
900-972 mA	Constant Current range
40 °C	Ambient Temperature
80 °C	Storage Temperature
75 °C	Max. Housing Temp.
IP20	Ingress Protection Code
2	Protection Class
20 %	Total Harmonic distortion
h	Calculated Lifetime
30000 h	Lifetime
5 a	Guarantee
118 mm	Dimensions
42 mm	width
28 mm	height
g	Weight
Ja	Shortcircuit proof
Ja	Overtemperature protection
Nein	Overvoltage Protection
	Switching cycles



as of: 22.09.2023

