


Datasheet
9205201

Netzteil Powerline Triac Panel CC 34W

Unser **Powerline Triac Konstantstromtreiber** sorgt für die Stromversorgung des Fled Backlit Panels. Mit einem Phasenan- oder -abschnittdimmer lässt sich der Treiber primär dimmen. Das Netzteil ist ENEC zertifiziert und sorgt für eine flickerfreie Ausleuchtung. Die angeschlossenen Leitungen minimieren den Installationsaufwand.



230 V	AC Voltage
50/60 Hz	Frequency Range
200-240 V	Voltage Range AC
V	Voltage Range DC
850,00 mA	AC Current
36,00 W	Rated Power
%	Full Load Efficiency
	Power Factor
W	Power at Standby
	Inrush Current
Triac-dimm	Dimming method
keine Hz	Radio frequency
0 kHz	PWM-frequency
40 V	Output voltage
0 %	Voltage Tolerance
0 W	Output Power
A	Output Current
mA	Constant Current range
45 °C	Ambient Temperature
80 °C	Storage Temperature
90 °C	Max. Housing Temp.
IP20	Ingress Protection Code
2	Protection Class
0 %	Total Harmonic distortion
h	Calculated Lifetime
h	Lifetime
5 a	Guarantee
138 mm	Dimensions
47 mm	width
30 mm	height
g	Weight
Ja	Shortcircuit proof
Ja	Overtemperature protection
Nein	Overvoltage Protection
50000	Switching cycles



as of: 17.11.2023

