


**Datasheet**  
**9205323**

**Netzteil Powerline DALI Panel CC 42W**

Unser **Powerline DALI Konstantstromtreiber** sorgt für die Stromversorgung des Fled Backlit Panels. Mit einem DALI-Bus lässt sich der Treiber ansteuern und dimmen. Das Netzteil ist ENEC und TÜV zertifiziert und sorgt für eine flickerfreie Ausleuchtung. Die angeschlossenen Leitungen minimieren den Installationsaufwand.



230 V	AC Voltage
50/60 Hz	Frequency Range
200-240 V	Voltage Range AC
6-38 V	Voltage Range DC
1100,00 mA	AC Current
47,30 W	Rated Power
87,00 %	Full Load Efficiency
0,95	Power Factor
0,50 W	Power at Standby
3,95A;180u	Inrush Current
DALI	Dimming method
keine Hz	Radio frequency
0 kHz	PWM-frequency
42 V	Output voltage
1 %	Voltage Tolerance
42 W	Output Power
0,25 A	Output Current
450-1100 mA	Constant Current range
45 °C	Ambient Temperature
80 °C	Storage Temperature
90 °C	Max. Housing Temp.
IP20	Ingress Protection Code
2	Protection Class
8 %	Total Harmonic distortion
h	Calculated Lifetime
100000 h	Lifetime
0 a	Guarantee
103 mm	Dimensions
68,5 mm	width
31 mm	height
g	Weight
Ja	Shortcircuit proof
Ja	Overtemperature protection
Nein	Overvoltage Protection
50000	Switching cycles



as of: 23.02.2024

